

Certification
Issued Under the Authority of the
Federal Communications Commission
By:

MiCOM Labs
 575 Boulder Court
 Pleasanton, CA 94566

Date of Grant: 10/29/2019
 Application Dated: 09/25/2019

Mikrotikls SIA
 Brivibas gatve 214i
 Riga, LV-1039
 Latvia

Attention: Edmunds Zvegincevs , engineer, R&D

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is
 VALID ONLY for the equipment identified hereon for use under the Commission's Rules
 and Regulations listed below.

FCC IDENTIFIER: TV7LHG5ACD
Name of Grantee: Mikrotikls SIA
Equipment Class: Unlicensed National Information Infrastructure TX
Notes: RBLHGG-5acD Wireless Module
Modular Type: Single Modular

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
MO	15E	5180.0 - 5240.0	0.051		
MO ND	15E	5260.0 - 5320.0	0.079		
MO ND	15E	5500.0 - 5720.0	0.049		
MO	15E	5745.0 - 5825.0	0.068		

C2PC to activate U-NII-2A and U-NII-2C bands, and enable DFS master functions using embedded software.

Single Modular Approval. Output power listed is maximum combined conducted power. Device is a 2x2 MIMO as is described in the filing. The antenna used with this transmitter must be installed to provide a minimum separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter, except in accordance with FCC multitransmitter product procedures. End-users must be provided with operating procedures for satisfying RF exposure compliance. This device contains 20, 40 and 80 MHz signal bandwidth.

MO: This Multiple Input Multiple Output (MIMO) device was evaluated for multiple transmitted signals as indicated in the filing.

ND: This UNII device complies with the Transmit Power Control (TPC) and Dynamic Frequency Selection (DFS) requirements in Section 15.407(h).